RESISTOR PLUS
SYNTHETIC ROOF UNDERLAYMENT

RESISTOR PLUS – SYNTHETIC ROOF UNDERLAYMENT is a 18-mil-thick synthetic roof underlayment membrane made of polyolefin. Stronger and lighter than most synthetics, RESISTOR PLUS is highly slip resistant, wet or dry, winter or summer.

Its UV protected, anti-skid surface allows a fast and safe installation in any condition. RESISTOR PLUS can even be installed during wintertime without losing any of its strength and flexibility.

RESISTOR Plus

THE PROFESSIONAL'S CHOICE

- 9 times lighter than felt
- 5 times stronger than felt
- Durable
- Easy to handle and install
- UV resistant
- Slip resistant
- Weather and mould resistant
- Puncture and tearing resistant
- Water repellent
- Resistance to work crew traffic
- No primer required

RESISTOR PLUS – SYNTHETIC ROOF UNDERLAYMENT

UPC Code:		40″ x 150':			6 23680 20556 7				
		12″ x 250':			6 23680 20802 5				
Product code	Dimensions	Thickness mm / mil	Approximate surface covered per roll		per box		per pallet		
			ft²	m²	ft²	m²	ft²	m²	
20556	40″ x 150' 1 m x 45.7 m	0.457/18	500	46.4	500	46.4	21,000	1,948.8	
20802	12″ x 250' 30 cm x 76.2 m	0.457/18	250	23.2	500	46.4	22,500	2,088	
Units per box:		40″ x 150':			1				
		12″ x 250':			2				
Box per pallet:		40″ x 150':			42				
		12″ x 250':			90				
Weight (±) per pallet:		40″ x 150':			630 lbs / 285.6 kg				
		12″ x 250':			675 lbs / 306 kg				

RESISTOR PLUS contains some ultraviolet inhibitors and is suitable for short-term outdoor applications. Suggested applications: non-permeable roofing membrane. TEST CONDUCTED BY INDEPENDENT LATORATORIES.

REQUIRED PRODUCT:
Nails with 1" washers (plastic or metal)

RESISTOR PLUS
SYNTHETIC
ROOF UNDERLAYMENT

THE PROFESSIONAL'S CHOICE

PRINTED IN CANADA • AR1 28-032008

RESISTO
WATERPROOFING SOLUTIONS

CUSTOMER SERVICE
1 877 478.8408
www.resisto.ca